
CIVIL ENGINEERING PLANS FOR UTSW BMES UTILITY RELOCATION CRAWFORD GRIGSBY SURVEY, ABSTRACT NO. 533 2330 INWOOD DRIVE, DALLAS TX

GENERAL NOTES (ALL DISCIPLINES):

- 1. PRIOR TO ANY CONSTRUCTION, THE CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE CONTRACT DOCUMENTS, SPECIFICATIONS AND PLANS, INCLUDING ALL NOTES, THE CITY OF DALLAS SPECIFICATIONS AND ANY OTHER APPLICABLE STANDARDS OR SPECIFICATIONS RELEVANT TO THE PROPER COMPLETION OF THE WORK SPECIFIED. FAILURE ON THE PART OF THE CONTRACTOR TO FAMILIARIZE HIMSELF WITH ALL STANDARDS OR SPECIFICATIONS PERTAINING TO THIS WORK SHALL IN NO WAY RELIEVE THE CONTRACTOR OF RESPONSIBILITY FOR PERFORMING THE WORK IN ACCORDANCE WITH ALL SUCH APPLICABLE STANDARDS AND SPECIFICATIONS.
- 2. CONTRACTOR SHALL HAVE IN HIS POSSESSION, PRIOR TO CONSTRUCTION, ALL NECESSARY PERMITS, LICENSES, ETC.
- 3. A STREET EXCAVATION PERMIT IS REQUIRED BEFORE WORK MAY BEGIN. APPLICATIONS MUST BE SUBMITTED IN ROOM 312, OAK CLIFF MUNICIPAL CENTER AT LEAST 48 HOURS (TWO WORKING DAYS) BEFORE BEGINNING CONSTRUCTION. FOR MORE INFORMATION CALL 214-948-4402, JOE SMETAK.
- 4. ALL MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION FOR NORTH CENTRAL TEXAS, LATEST EDITION, AND THE CITY OF DALLAS MOBILITY AND STREET SERVICES DEPARTMENT ADDENDUM.
- 5. DURING THE CONSTRUCTION OF THESE IMPROVEMENTS, ANY INTERPRETATION OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION FOR NORTH CENTRAL TEXAS, AND ANY MATTER WHICH REQUIRES THE APPROVAL OF THE OWNER, MUST BE APPROVED BY THE DIRECTOR OF MOBILITY AND STREET SERVICES DEPARTMENT OR HIS DESIGNEE BEFORE ANY CONSTRUCTION INVOLVING THAT DECISION COMMENCES. ASSUMPTIONS ABOUT WHAT THESE DECISIONS MIGHT BE WHICH ARE MADE DURING THE BIDDING PHASE WILL HAVE NO BEARING ON THE DECISION.
- 7. FOR ADJUSTMENT OF DALLAS WATER UTILITIES APPURTENANCES OR TO VERIFY LOCATIONS OF EXISTING WATER AND WASTEWATER MAINS IN AREA, CALL 214-670-1770 AT LEAST (3) THREE WORKING DAYS PRIOR TO CONSTRUCTION.
- 8. STREETS, ALLEYS, SIDEWALKS, DRIVEWAYS, AND STORM DRAINAGE FACILITIES IN THE PUBLIC RIGHT-OF-WAY SHALL BE CONSTRUCTED IN CONFORMANCE WITH THE CITY OF DALLAS, STANDARD CONSTRUCTION DETAILS, FILE 251D-1, LATEST EDITION.
- 9. ALL CONCRETE FOR PAVEMENT SHALL BE 4000 PSI FOR MACHINE FINISH AND 4500 PSI IF IT IS NECESSARY FOR HAND FINISH.
- 10. USE OF FLY ASH OR ANY CHEMICAL ADMIXTURE IN CONCRETE WILL REQUIRE PRIOR APPROVAL FROM THE DIRECTOR OF PUBLIC WORKS AND TRANSPORTATION AND WILL BE SUBJECT TO SPECIAL MONITORING AND INSPECTION OF THE WORK AS PROVIDED IN THE CITY OF DALLAS ADDENDUM TO THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION FOR NORTH CENTRAL TEXAS. FLY ASH SHALL NOT BE USED IN HAND FINISH CONCRETE.
- 11. CONSTRUCTION INSPECTION WILL BE PERFORMED BY REPRESENTATIVES OF THE OWNER, ENGINEER, GEOTECHNICAL ENGINEER, AND REVIEWING AUTHORITIES AND AGENCIES. UNRESTRICTED ACCESS SHALL BE PROVIDED TO THEM AT ALL TIMES. CONTRACTOR IS RESPONSIBLE FOR UNDERSTANDING AND SCHEDULING REQUIRED INSPECTIONS.
- 12. CERTAIN CONSTRUCTION STAKING MAY BE PERFORMED BY THE OWNER'S SURVEYOR. SEE THE CONTRACT DOCUMENTS FOR DETAILS OF THIS SERVICE.
- 13. IF UNFORESEEN PROBLEMS OR CONFLICTS ARE ENCOUNTERED IN THE CONSTRUCTION, FOR WHICH AN IMMEDIATE SOLUTION IS NOT APPARENT, THE ENGINEER AND OWNER SHALL BE NOTIFIED IMMEDIATELY.
- 14. OTHER CONSTRUCTION WILL BE UNDERWAY AT THE SAME TIME AND IN THE SAME GENERAL AREA WHICH IS ENCOMPASSED BY THIS CONTRACT. THIS CONTRACTOR SHALL COORDINATE WITH OTHER CONTRACTORS TO ESTABLISH A CONSTRUCTION SEQUENCE WHICH WILL CAUSE THE LEAST HINDRANCE TO ALL.
- 15. IT WILL BE THE RESPONSIBILITY OF EACH CONTRACTOR TO PROTECT ALL EXISTING PUBLIC AND PRIVATE UTILITIES THROUGHOUT THE CONSTRUCTION OF THIS PROJECT. CONTRACTOR SHALL CONTACT THE APPROPRIATE UTILITY COMPANIES FOR LINE LOCATIONS AT LEAST 48 HOURS PRIOR TO COMMENCEMENT OF CONSTRUCTION AND SHALL ASSUME FULL LIABILITY TO THOSE COMPANIES FOR ANY DAMAGES CAUSED TO THEIR FACILITIES. CONTACT THE CITY OF DALLAS AT LEAST (3) THREE WORKING DAYS PRIOR TO CONSTRUCTION FOR ALL CITY RELATED IMPROVEMENTS.

CITY OF DALLAS LINE LOCATE	311
CITY OF DALLAS, PUBLIC WORKS INSPECTION	214-948-4290 OR 214-670-5313
DWU CONSTRUCTION INSPECTION	214–670–8109
DWU, WASTEWATER COLLECTION DIVISION	214–670–8003
FRANCHISE UTILITIES	TEXAS 811

- 16. ALL CONTRACTORS MUST CONFINE THEIR ACTIVITIES TO THE WORK AREA. NO ENCROACHMENTS ONTO ADJACENT PROPERTIES WILL BE ALLOWED UNLESS SPECIFIED IN THE PLANS. ANY DAMAGE RESULTING THEREFROM SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO REPAIR.
- 17. THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES ARE SHOWN IN AN APPROXIMATE WAY ONLY AND HAVE NOT BEEN INDEPENDENTLY VERIFIED BY THE OWNER OR ITS REPRESENTATIVE. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK, AND AGREES TO BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT BE OCCASIONED BY THE CONTRACTOR'S FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL UNDERGROUND UTILITIES.
- 18. A TRAFFIC CONTROL PLAN (TCP) MUST BE SUBMITTED TO THE DEPARTMENT OF TRANSPORTATION FOR REVIEW AND APPROVAL BY THE TRAFFIC SAFETY COORDINATORS PRIOR TO CONSTRUCTION. NO TRAFFIC LANE OR SIDEWALK ALONG THE PUBLIC STREET OR ALLEY IS TO BE CLOSED WITHOUT FIRST OBTAINING THE APPROPRIATE PERMIT(S). CLOSURE OF ANY TRAFFIC LANE MUST BE RESTRICTED TO THE HOURS OF 9:00 A.M. TO 3:30 P.M. WORKDAYS. CONTRACTOR MUST CALL (214)-670-6904 TO OBTAIN A PERMIT.



OWNER



Juan M. Guerra, Jr., P.E. juan.guerra@utsouthwestern.edu 5323 Harry Hines Blvd Dallas, Texas 75390 Phone: 214-648-2400 CIVIL ENGINEER James D. Davis, P.E. jdavis@walterpmoore.com

MARTINEZ MOORE ENGINEERS MARTINEZ MOORE ENGINEERS, LLC 221 WEST 6TH ST., SUITE 800 AUSTIN, TX 78701 PHONE: 512-330-1278



Walter P Moore and Associates, Inc. 500 North Akard Street, Suite 2300 Dallas, Texas 75201 TBPE Firm Registration No. 1856 214.740.6200

SURVEYOR

Kyle Harris, RPLS


Pacheco Koch 7557 Rambler Road, Suite 1400 Dallas, Tx 75231


Phone: (972)-235-3031 kharris@pkce.com


	CONTRACT
CONTRACT NO.	
CONTRACTOR	


	PLANS, PROFILES AN	ID DETAILS APPROVED FOR THIS PROJECT
FILE	SHEETS	DESCRIPTION
311T-XXXX	C01	COVER SHEET
311T-XXXX	C04.01	EXISTING CONDITIONS PLAN
311T–XXXX	C04.02	DEMOLITION PLAN
311T-XXXX	C04.03	UTILITY DEMOLITION PLAN
311T-XXXX	C08.01	EX. DRAINAGE AREA MAP
311T-XXXX	C08.02	PROP. DRAINAGE AREA MAP
311T-XXXX	C08.03	OFFSITE DRAINAGE AREA MAP
311T-XXXX	C08.04	DRAINAGE CALCULATIONS
311T-XXXX	C09.01	STORM SEWER PLAN OVERALL
311T-XXXX	C09.02	STORM SEWER PLAN
311T-XXXX	C09.03	STORM SEWER PLAN
311T-XXXX	C09.04	STORM SEWER PLAN
311T-XXXX	C09.05	STORM SEWER PLAN
311T-XXXX	C09.06	STORM SEWER PROFILE
311T-XXXX	C09.07	STORM SEWER PROFILE
311T-XXXX	C09.08	STORM SEWER PROFILE
311T-XXXX	C09.09	STORM SEWER PROFILE
311T-XXXX	C09.50	STORM SEWER DETAILS
411Q-XXXX	C10.01	WATER & WASTEWATER OVERALL PLAN
411Q-XXXX	C10.02	WATER & WASTEWATER PLAN
411Q-XXXX	C10.03	WATER & WASTEWATER PLAN
411Q-XXXX	C10.04	WATER & WASTEWATER PLAN
411Q-XXXX	C10.05	WATER & WASTEWATER PLAN WASTEWATER PROFILE
411Q-XXXX	C10.06	EROSION CONTROL PLAN
311T-XXXX	C11.01	EROSION CONTROL PLAN EROSION CONTROL DETAILS
311T-XXXX	C11.50 SET	CITY OF DALLAS DEPARTMENT OF PUBLIC WORKS STANDARD
251D-1	JEI	CONSTRUCTION DETAILS, UPDATED: SEPT 2002
		CUNJIKUCIIUN DEIAILJ, UPDAIED: JEPI ZUUZ

	REV NO.	DA 02/24/	2021	REVIS	DESCRIPTI	VEZ MOORE ENG WEST 6TH ST., S	- , -
Anne 2/2/2021	MARTINEZ MOORE MARTINEZ MOORE 221 WEST 6TH ST., SUITE 8 221 WEST 6TH ST., SUITE 8 AUSTIN, TX 78701 PHONE: 512-330-1278 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING TRA N/A N/A WW21-XXX D COVER SHEET				1278		
* JAMES D. DAVIS JR 91256	UTSW BMES UTILITY RELOCATION 2300 INWOOD DRIVE						
Walter P. Moore and Associates, Inc. TBPE Firm Registration No. 1856	CRAWFORD GRIGSBY SURVEY ABSTRACT NO. 533						
<u>INFORMATION</u>	SUSTAINABLE DEVELOPMENT & CONSTRUCTION CITY OF DALLAS, DALLAS COUNTY, TEXAS						
DATE	DESIGN	DRAWN		DATE RUARY	FILE	NUMBER	SHEET
	JDD	VDA		RUAR I 2021	311T	XXXX	C01










DEMOLITION NOTES

- KOCH, LLC DATED NOVEMBER 2, 2020.
- 2. EXISTING UTILITY INFORMATION IS BASED ON SEVERAL SOURCES INCLUDING A SURVEY ON CALL SERVICE TO LOCATE PUBLIC OR FRANCHISE SUBSURFACE UTILITIES PRIOR TO ANY
- 3. ALL DEMOLITION DEBRIS TO BE DISPOSED OF LEGALLY IN A PERMITTED DISPOSAL FACILITY.
- 4. LOCATIONS OF EXISTING STRUCTURES AND PAVEMENT TO BE REMOVED ARE APPROXIMATE AND ARE SHOWN FOR REFERENCE. CONTRACTOR IS RESPONSIBLE FOR IDENTIFYING THE NUMBER, TYPE, AND SIZE OF ALL STRUCTURES TO BE REMOVED.
- REQUIRED FOR SITE DEMOLITION.
- 6. THE CONTRACTOR SHALL CONTACT EACH UTILITY COMPANY PRIOR TO DEMOLITION TO
- 7. REFER TO THE CITY OF DALLAS, DEPARTMENT OF PUBLIC WORKS AND TRANSPORTATION
- 8. CONTRACTOR TO PROVIDE TRAFFIC CONTROL FOR ALL WORK WITHIN PUBLIC RIGHTS-OF-WAY DURING DEMOLITION.
- 10. REFER TO SHEET C4.10 UTILITY DEMOLITION PLAN FOR REMOVAL OF EXISTING PUBLIC AND
- 11. A STREET EXCAVATION PERMIT IS REQUIRED BEFORE WORK MAY BEGIN. APPLICATIONS MUST BE SUBMITTED IN ROOM 312, OAK CLIFF MUNICIPAL CENTER AT LEAST 48 HOURS
- 12. ALL MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE STANDARD SPECIFICATIONS CITY OF DALLAS DEPARTMENT OF PUBLIC WORKS AND TRANSPORTATION ADDENDUM.
- 13. DURING THE CONSTRUCTION OF THESE IMPROVEMENTS, ANY INTERPRETATION OF THE
- 14. FOR ADJUSTMENT OF DALLAS WATER UTILITIES APPURTENANCES OR TO VERIFY LOCATIONS THREE WORKING DAYS PRIOR TO CONSTRUCTION.
- STANDARD CONSTRUCTION DETAILS, FILE 251D-1, LATEST EDITION.
- 16. ALL CONCRETE FOR PAVEMENT WITHIN THE PUBLIC RIGHT-OF-WAY SHALL BE 4000 PSI FOR MACHINE FINISH AND 4500 PSI IF IT IS NECESSARY FOR HAND FINISH.
- 17. NO TRAFFIC LANE OR SIDEWALK ALONG ANY PUBLIC STREET OR ALLEY IS TO BE CLOSED WITHOUT FIRST OBTAINING THE APPROPRIATE PERMIT(S) FROM PAUL THOMPSON OR LANE MUST BE RESTRICTED TO THE HOURS OF 9:00 A.M. TO 3:30 P.M. WORKDAYS.
- 18. SAWCUT LINES SHOWN ON THE DESIGN PLANS FOR THE REMOVAL AND REPLACEMENT OF CONCRETE PAVEMENT, DRIVES, SLABS, SIDEWALKS, ETC. ARE FOR INFORMATIONAL PURPOSES ONLY. IF PAVEMENT IS MORE THAN 5 YEARS OLD, THE PAVEMENT CUT AND THE ENTIRE CONCRETE PANEL MUST BE REPLACED.

	CONTRACT
CONTRACT NO.	
CONTRACTOR	



LEGEND ____ BM# $\mathbf{\Theta}$ _____O^{SS}____ _____4"G— _____ — _ _ E2 — X —

DEMOLITION NOTES

- BOUNDARY AND TOPOGRAPHIC INFORMATION WAS OBTAINED FROM SURVEY BY PACHECO KOCH, LLC DATED NOVEMBER 2, 2020.
- 2. EXISTING UTILITY INFORMATION IS BASED ON SEVERAL SOURCES INCLUDING A SURVEY ON THE GROUND OF IMPROVEMENTS VISIBLE ON THE SURFACE AND AS-BUILT DRAWINGS. WHILE EVERY ATTEMPT WAS MADE TO ACCURATELY DEPICT THE EXISTING UTILITIES, SOME UTILITIES MAY EXIST THAT ARE NOT DOCUMENTED. THE CONTRACTOR IS CAUTIONED TO USE A ONE CALL SERVICE TO LOCATE PUBLIC OR FRANCHISE SUBSURFACE UTILITIES PRIOR TO ANY EXCAVATION ACTIVITIES.
- 3. ALL DEMOLITION DEBRIS TO BE DISPOSED OF LEGALLY IN A PERMITTED DISPOSAL FACILITY.
- 4. LOCATIONS OF EXISTING STRUCTURES AND PAVEMENT TO BE REMOVED ARE APPROXIMATE AND ARE SHOWN FOR REFERENCE. CONTRACTOR IS RESPONSIBLE FOR IDENTIFYING THE NUMBER, TYPE, AND SIZE OF ALL STRUCTURES TO BE REMOVED.
- 5. THE CONTRACTOR IS RESPONSIBLE FOR IDENTIFYING AND OBTAINING ALL PERMITS THAT ARE REQUIRED FOR SITE DEMOLITION.
- 6. THE CONTRACTOR SHALL CONTACT EACH UTILITY COMPANY PRIOR TO DEMOLITION TO COORDINATE THE DISCONNECTION/RELOCATION OF UTILITY SERVICES.
- 7. REFER TO THE CITY OF DALLAS, DEPARTMENT OF PUBLIC WORKS AND TRANSPORTATION "PAVEMENT CUT AND REPAIR STANDARDS MANUAL" LATEST EDITION FOR ALL SAWCUT AND REPAIR REQUIREMENTS
- 8. CONTRACTOR TO PROVIDE TRAFFIC CONTROL FOR ALL WORK WITHIN PUBLIC RIGHTS-OF-WAY DURING DEMOLITION.
- 9. REFER TO EROSION CONTROL PLAN FOR MEASURES TO BE INSTALLED PRIOR TO DEMOLITION BEGINNING.
- 10. REFER TO SHEET C4.10 UTILITY DEMOLITION PLAN FOR REMOVAL OF EXISTING PUBLIC AND PRIVATE UTILITIES.
- 11. A STREET EXCAVATION PERMIT IS REQUIRED BEFORE WORK MAY BEGIN. APPLICATIONS MUST BE SUBMITTED IN ROOM 312, OAK CLIFF MUNICIPAL CENTER AT LEAST 48 HOUR (TWO WORKING DAYS) BEFORE BEGINNING CONSTRUCTION. FOR MORE INFORMATION CALL 214-948-4042.
- 12. ALL MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION FOR NORTH CENTRAL TEXAS, LATEST EDITION, AND THE CITY OF DALLAS DEPARTMENT OF PUBLIC WORKS AND TRANSPORTATION ADDENDUM.
- 13. DURING THE CONSTRUCTION OF THESE IMPROVEMENTS, ANY INTERPRETATION OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION FOR NORTH CENTRAL TEXAS, AND ANY MATTER WHICH REQUIRES THE APPROVAL OF THE OWNER, MUST BE APPROVED BY THE DIRECTOR OF PUBLIC WORKS AND TRANSPORTATION OR HIS DESIGNEE BEFORE ANY CONSTRUCTION INVOLVING THAT DECISION COMMENCES. ASSUMPTIONS ABOUT WHAT THESE DECISIONS MIGHT BE WHICH ARE MADE DURING THE BIDDING PHASE WILL HAVE NO BEARING ON THE DECISION.
- 14. FOR ADJUSTMENT OF DALLAS WATER UTILITIES APPURTENANCES OR TO VERIFY LOCATIONS OF EXISTING WATER AND WASTEWATER MAINS IN AREA, CALL 214-670-1770 AT LEAST (3) THREE WORKING DAYS PRIOR TO CONSTRUCTION.
- 15. STREETS, ALLEYS, SIDEWALKS, DRIVEWAYS, AND STORM DRAINAGE FACILITIES IN THE PUBLIC RIGHT-OF-WAY SHALL BE CONSTRUCTED IN CONFORMANCE WITH THE CITY OF DALLAS, STANDARD CONSTRUCTION DETAILS, FILE 251D-1, LATEST EDITION.
- 16. ALL CONCRETE FOR PAVEMENT WITHIN THE PUBLIC RIGHT-OF-WAY SHALL BE 4000 PSI FOR MACHINE FINISH AND 4500 PSI IF IT IS NECESSARY FOR HAND FINISH.
- 17. NO TRAFFIC LANE OR SIDEWALK ALONG ANY PUBLIC STREET OR ALLEY IS TO BE CLOSED WITHOUT FIRST OBTAINING THE APPROPRIATE PERMIT(S) FROM PAUL THOMPSON OR RUSSELL FINLEY WITH THE CITY OF DALLAS (214-670-5896). CLOSURE OF ANY TRAFFIC LANE MUST BE RESTRICTED TO THE HOURS OF 9:00 A.M. TO 3:30 P.M. WORKDAYS.
- 18. SAWCUT LINES SHOWN ON THE DESIGN PLANS FOR THE REMOVAL AND REPLACEMENT OF CONCRETE PAVEMENT, DRIVES, SLABS, SIDEWALKS, ETC. ARE FOR INFORMATIONAL PURPOSES ONLY. IF PAVEMENT IS MORE THAN 5 YEARS OLD, THE PAVEMENT CUT AND REPAIR STANDARDS MANUAL MUST BE FOLLOWED. IF PAVEMENT IS 5 YEARS OLD OR LESS, THE ENTIRE CONCRETE PANEL MUST BE REPLACED.

	CONTRACT
CONTRACT NO.	
CONTRACTOR	

	PROPERTY LINE	
	EXISTING EASEMENT	
¥ 1	BENCHMARK	
Z	EX. STORM SEWER/MH	
	EX. CURB INLET	
	EX. WASTEWATER/MH/CLEANOUT	
94/0	EX. WATER/FIRE HYDRANT/VALVE	
	EX. GAS	
E2 ——	EX. ELECTRIC	
— C2 —	EX. COMMUNICATION	
	EX. FENCE	

 $\boldsymbol{\aleph}$

JAMES D. DAVIS JR

91256

KICENSED. SIONALEN

Walter P. Moore and Associates, Inc.

TBPE Firm Registration No. 1856

DATE

INFORMATION

Annut an

1,2/2/2024

REV NO.

PLAT NO.

N/A

DESIGN

JDD

VDA


FEBRUARY


2021

311T

XXXX


C04.03






DA	AREA (ac)	C	t _c (min)	I ₁₀₀ (in/hr)	Q100 (cf
A1	2.50	0.9	10	9.60	21.60
A2	0.35	0.9	10	9.60	3.02
A3	0.08	0.9	10	9.60	0.69
A4	0.61	0.9	10	9.60	5.27
A5	0.70	0.9	10	9.60	6.05
A6	0.05	0.9	10	9.60	0.43
A7	0.10	0.9	10	9.60	0.86
A8	0.43	0.9	10	9.60	3.72
A9	0.92	0.9	10	9.60	7.95
A10	0.73	0.9	10	9.60	6.31
A11	0.20	0.9	10	9.60	1.73
A12	1.08	0.9	10	9.60	9.33
A13	0.69	0.9	10	9.60	5.96
OS1	7.04	0.9	10	9.60	60.83
OS2	1.93	0.9	10	9.60	16.68
OS3	3.86	0.9	10	9.60	33.35
OS4	6.58	0.9	<mark>10</mark>	9.60	56.85
OS5	<mark>6.01</mark>	0.9	10	9.60	51.93


CONTRACT NO. CONTRACTOR







						_
DA	AREA (ac)	С	t _c (min)	I ₁₀₀ (in/hr)) Q ₁₀₀ (cfs)	
A1	2.81	0.9	10	9.60	24.28	T
A2	0.36	0.9	10	9.60	3.11	Τ
A3	0.07	0.9	10	9.60	0.60	T
A4	0.61	0.9	10	9.60	5.27	
A5	0.69	0.9	10	9.60	5.96	Ι
A6	0.50	0.9	10	9.60	4.32	
A7	0.44	0.9	10	9.60	3.80	
A8	0.43	0.9	10	9.60	3.72	T
A9	0.42	0.9	10	9.60	3.63	Ι
A10	0.47	0.9	10	9.60	4.06	Τ
A11	0.93	0.9	10	9.60	8.04	
A12	0.69	0.9	10	9.60	5.96	
OS1	7.04	0.9	10	9.60	60.83	Ι
OS2	1.93	0.9	10	9.60	16.68	Ι
OS3	3.86	0.9	10	9.60	33.35	Τ
OS4	6.58	0.9	10	9.60	56.85	
OS5	6.01	0.9	10	9.60	<mark>51.93</mark>	
						_
		DEEED TA	CUEET	CUO US (VEECITE L	١Γ

	CONTRACT
CONTRACT NO.	
CONTRACTOR	








BENCH	BENCHMARKS:						
BM# 795	A STANDARD WATER DEPARTMENT BENCH MARK SET ON CONCRETE CURB OF STORM SEWER DROP INLET ON THE SOUTHEAST CORNER OF THE INTERSECTION. ESTABLISHED GRID ELEVATION : 442.880 RECORDED GRID ELEVATION : 442.74						
BM# 802	A SQUARE IS CUT ON CENTER OF CONCRETE CURB ON INLET NORTH SIDE OF IRVING BOULEVARD IN FRONT OF BUILDING #2780 IRVING BOULEVARD. ESTABLISHED GRID ELEVATION : 403.78 RECORDED GRID ELEVATION : 403.77						
BM# 1	" X " CUT SET ON THE SOUTHEAST EDGE OF A CONCRETE SIDEWALK, ±115 FEET NORTH OF THE NORTHEAST BUILDING CORNER, ±130 FEET SOUTH OF THE CENTERLINE OF INWOOD ROAD AND ±33 FEET WEST OF A CONCRETE DRIVE ENTRANCE. N: 6985868.26, E: 2479190.00, ELEVATION : 445.274						
BM# 3	" X " CUT SET ON A CONCRETE MEDIAN IN INWOOD ROAD, ±300 FEET NORTHEAST OF THE INTERSECTION OF FOREST PARK ROAD AND INWOOD ROAD. N:6986021.72 , E: 2479156.92 , ELEVATION: 440.327						

	CALL BEFORE YOU TEXAS ONE CALL PARTICIPANTS 48 HOURS NOTICE BEFORE YOU OR BLAST - STOP CALL Texas One Call Sy CALL 811						pants request you dig, drill, op call I System	
				REVIS	SIONS			
	REV NO.	DAT	:		DESCRIPTI	ON	BY	
		02/24/2	021	ISSUE F	OR BID			
MARTINEZ MOC					MARTINEZ MOORE ENGINEERS, LLC 221 WEST 6TH ST., SUITE 800 AUSTIN, TX 78701 PHONE: 512-330-1278			
	PLAT N	O. BL		RMIT NO.			RACKING NOS.	
SAMMAD in	N/A			/A	WW21-		DP21-XXXX	
AN AF 15+ 9 1, 212 2021		OFFS	ITE	DRAIN	NAGE AF	REA MA	>	
* * *		UTSW	BME	S UTI	LITY REI)N	
JAMES D. DAVIS JR 91256 م		2	300	INWO	OD DRIV	Έ		
CENSED.		CRAW	FOF	RD GRI	GSBY S	URVEY		
			ABS	TRAC	T NO. 53	3		
Walter P. Moore and Associates, Inc. TBPE Firm Registration No. 1856	SUSTAINABLE DEVELOPMENT & CONSTRUCTION						RUCTION	
INFORMATION	CITY OF DALLAS, DALLAS COUNTY, TEXAS							
DATE	DESIGN	DRAWN	1	DATE	FILE	NUMBER	SHEET	

									-						57	FORM DRAI	N SYSTEM	CALCULA								_					
RUNOFF CC POINT (IN MANH	ILET OR		INCREMENT/	L DRAINAGI	AREA															HY DRAULIC ELEV.											
UPSTREAM STATION	Downstre Am Station	DISTANCE	AREA NO.	DRAINAGE AREA "A"	Total Area	RUNOFF COEFF. "C"	INCREMENT AL "CA"	A COUMUL- ATED "CA"	TIME AT UPSTREAM STATION	FLOW TIME	TIME AT D/S STATION	STORM FREQUENC Y	INTENSITY "I"	RUNOFF "Q"	STORM SEWER SIZE		SLOPE OF HYDRAULIC GRADIENT "S"	Box Si	ze (ft^2)	UP STREAM	DOWN STREAM	INFLOW VELOCITY "V 1"	OUTFLOW VELOCITY "V2"	VELOCITY HEAD VH1	VELOCITY HEAD VH2	Loss Coeff K	KxVH1	FRICTION HEAD LOSS IN PIPE "L"x"S"		HEAD LOSS Hj	Elevation 5 of desig point
		(FT)		(ACRES)	(ACRES)				(MIN)	(MIN)	(MIN)	(YEARS)	(IN/HR)	(CFS)	(ℕ)		(FT/FT)	Н	W			(FPS)	(FPS)	(FT)	(FT)			(FT)			m.s.l
2	1	3	4	4	5	6	7	8	18	19	20	9	9	10	11	12	13	11	11	27	26	15	14	17	17	21	22	16		23	25
Line A																															
911.00	776.00	135.00	A2 & OS3	4.22	4.22	0.90	3.80	3.80	10.00	0.44	10.44	100.00	9.60	36.46	36.00	0.013	0.0030	-	-	445.93	445.53	0.00	5.16	0.00	0.41	1.50	0.00	0.41	Equ. 1	0.41	446.3
776.00	694.33	81.67	-	0.00	4.22	0.90	0.00	3.80	10.44	0.27	10.70	100.00	9.46	35.94	36.00	0.013	0.0029	-	-	445.43	445.19	5.16	5.09	0.41	0.40	0.25	0.10	0.24	Equ. 2	0.10	445.5
694.33	633.04	61.29	A3	0.07	4.29	0.90	0.06	3.86	10.70	0.20	10.90	100.00	9.38	36.22	36.00	0.013	0.0030	2 -	-	445.08	444.90	5.09	5.12	0.40	0.41	0.25	0.10	0.18	Equ. 2	0.10	445.1
633.04	512.00	121.04	A4, OS1 & OS2	9.58	13.87	0.90	8.62	12.48	10.90	0.28	11.18	100.00	9.32	116.32	54.00	0.013	0.0035	-	-	444.69	444.27	5.12	7.31	0.41	0.83	0.25	0.10	0.43	Equ. 2	0.21	444.9
512.00	493.98	18.02	A5	0.69	14.56	0.90	0.62	13.10	11.18	0.05	11.23	100.00	9.23	120.98	60.00	0.013	0.0022		-	443.97	443.93	7.31	6.16	0.83	0.59	0.35	0.29	0.04	Equ. 1	0.30	444.2
493.98	419.27	74.71	Half of A8	0.22	14.78	0.90	0.19	13.30	11.23	0.20	11.43	100.00	9.22	122.56	60.00	0.013	0.0022	-	-	443.53	443.36	6.16	6.24	0.59	0.61	0.35	0.21	0.17	Equ. 1	0.40	443.9
419.27	398.60	20.67	A6	0.50	15.28	0.90	0.45	13.75	11.43	0.05	11.48	100.00	9.15	125.85	60.00	0.013	0.0024	-	-	443.53	442.89	6.24	6.41	0.61	0.64	0.35	0.21	0.05	Equ. 1	0.43	443.3
398.60	333.56	65.04	A7	0.44	15.72	0.90	0.40	14.14	11.48	0.16	11.65	100.00	9.14	129.24	60.00	0.013	0.0025	-	-	443.93	442.28	6.41	6.58	0.64	0.67	0.35	0.22	0.16	Equ. 1	0.45	442.8
333.56	280.17	53.39	A9	0.42	16.14	0.90	0.38	14.52	11.65	0.13	11.78	100.00	9.09	131.95	60.00	0.013	0.0026	-	-	441.81	441.67	6.58	6.72	0.67	0.70	0.35	0.24	0.14	Equ. 1	0.47	442.2
280.17	210.62	69.55	Half of A8	0.22	16.35	0.90	0.19	14.72	11.78	0.17	11.95	100.00	9.05	133.10	60.00	0.013	0.0026	-	-	441.21	441.02	6.72	6.78	0.70	0.71	0.35	0.25	0.18	Equ. 1	0.47	441.6
210.62	166.37	44.25	A10	0.47	16.82	0.90	0.42	15.14	11.95	0.11	12.06	100.00	8.99	136.12	60.00	0.013	0.0028	-	-	440.53	440.41	6.78	6.93	0.71	0.75	0.35	0.25	0.12	Equ. 1	0.50	441.0
166.37	102.23	64.14	A1 & A11	3.74	20.56	0.90	3.37	18.50	12.06	0.13	12.18	100.00	8.96	165.77	60.00	0.013	0.0041	-	-	439.56	439.30	6.93	8.44	0.75	1.11	0.35	0.26	0.26	Equ. 1	0.85	440.4
102.23	0.00	102.23	-	0.00	20.56	0.90	0.00	18.50	12.18	0.20	12.38	100.00	8.92	165.04	60.00	0.013	0.0040	3-	-	439.02	438.61	26.00	8.41	10.50	1.10	0.25	2.62	0.41	Equ. 2	0.27	439.3 438.6
Line R																															
Line B 596.74	287.18	309.56	OS5 & OS6	86.84	86.84	0.90	78.16	78.16	21.26	0.53	21.79	100.00	7.01	547.48		0.013	0.0032	7.00	8.00	440.15	439.17	0.00	9.78	0.00	1.48	0.25	0.00	0.98	Equ. 2	0.37	440.5
287.18	0.00	287.18	-	0.00	86.84	0.90	0.00	78.10	21.20	0.50	22.28	100.00	6.92	540.64	-	0.013	0.0032	7.00	8.00	438.81	437.93	9.78	9.65	1.48	1.48	0.25	0.37	0.88	Equ. 2	0.37	439.1
207.10	0.00	207.10		0.00	00.04	0.50	0.00	70.10	21.75	0.50	22.20	100.00	0.52	540.04		0.015	0.0051	7.00	0.00	430.01	457.55	5.78	5.05	1.40	1.45	0.25	0.57	0.00	Lyu, z	0.50	437.9
	LINE A BE	GINNING 1	00-YR HGL OF 43	38.61 WAS	OBTAINED	FROM STA	TION 1+99.	.00 LINE "A	" FROM SC	OUTHWEST	ERN MEDIC	AL CENTER	R, FILE 311	T-7628, SHE	ET 11 PREF	ARED BY CH	ARLES GO	JER AND A	SSOCIATE	E <mark>S, INC., DA</mark>	TED JUNE 1	9, 2008. TH	IIS WAS CO	MPARED T	O THE 100-	YEAR ELEV	ATION OF	437.93			
	FROMCR	OSS SECTIO	N 7027 OF THE	KNIGHTS B	RANCH DR.	AINAGE R	EPORT BY H	ALFF ASSC	CIATES INC	C, DATED J	ANUARY 25	, 2007. THI	E HIGHEST	ELEVATION	WAS USE	D.															

	CONTRACT
CONTRACT NO.	
CONTRACTOR	

varian HG COMMENTS ON K FREE FG r design point I I 25 I I 1 I I 146.35 EX WYE INLET 5.37 451.30 145.53 MANHOLE 6.07 451.50 145.19 GRATE INLET 5.86 450.94 144.39 JUNCTION BOX 1.47 446.16 144.39 JUNCTION BOX 1.47 446.65 144.39 GO DEG WYE 2.61 446.50 1442.88 60 DEG WYE 2.73 446.66 142.28 60 DEG WYE 5.27 447.08 141.02 60 DEG WYE 5.27 444.80 141.02 60 DEG WYE 5.27 446.82 143.36 60 DEG WYE 5.27 446.82 143.36 10 DEG WYE 5.27 446.82 143.36 10 DEG WYE 5.27 446.82 143.36 10 DEG WYE 7.29 446.82 133.30 JUNCTION BOX 7.80 446.82 138.61 I <td< th=""><th>APSCO 34-T</th></td<>	APSCO 34-T
ration HG COMMENTS ON K FREE-BOARD FG proint rms.1. rms.1. rms.1. 25 rms.1. rms.1. rms.1. 25 rms.1. rms.1. rms.1. 26 rms.1. rms.1. rms.1. 27 rms.1. rms.1. rms.1. 28 rms.1. rms.1. rms.1. 29 rms.1. rms.1. rms.1. 29 rms.1. rms.1. rms.1. 29 rms.1. rms.1. rms.1. 20 rms.1. rms.1. rms.1. 20 rms.1. rms.1. rms.1. 20 rms.1. rms.1. rms.1. 21 rms.1. rms.1. rms.1. rms.1. 22 rms.1. rms.1. rms.1. rms.1. 23 rms.1. rms.1. rms.1. rms.1. 241.0.20 rms.1. rms.2. rms.2. rms.2. 241.6.7 rms.2. rms.2. rms.2. rms.2. 241.6.22 <t< th=""><th></th></t<>	
varian HG COMMENTS ON K FREE FG r design point I I I 25 I I I 146.35 EX WYE INLET 5.37 451.30 145.53 MANHOLE 6.07 451.50 145.19 GRATE INLET 5.86 450.94 144.30 JUNCTION BOX 1.47 446.16 144.33 60 DEG WYE 2.61 446.50 143.36 60 DEG WYE 2.73 446.66 142.28 60 DEG WYE 2.73 446.66 142.28 60 DEG WYE 5.27 447.08 144.28 60 DEG WYE 5.27 446.85 142.28 60 DEG WYE 5.27 446.82 143.36 60 DEG WYE 5.27 446.85 144.28 100 60 DEG WYE 4.27 144.83 100 7.29 446.82 133.86 I I I 140.52 JUNCTION BOX 10.00 450.15 133.91 90 DEG BEND 6.54 445.35 <	
varian HG COMMENTS ON K FREE FG r design point I I 25 I I 1 I I 146.35 EX WYE INLET 5.37 451.30 145.53 MANHOLE 6.07 451.50 145.19 GRATE INLET 5.86 450.94 144.39 JUNCTION BOX 1.47 446.16 144.39 JUNCTION BOX 1.47 446.65 144.39 GO DEG WYE 2.61 446.50 1442.88 60 DEG WYE 2.73 446.66 142.28 60 DEG WYE 5.27 447.08 141.02 60 DEG WYE 5.27 444.80 141.02 60 DEG WYE 5.27 446.82 143.36 60 DEG WYE 5.27 446.82 143.36 10 DEG WYE 5.27 446.82 143.36 10 DEG WYE 5.27 446.82 143.36 10 DEG WYE 7.29 446.82 133.30 JUNCTION BOX 7.80 446.82 138.61 I <td< th=""><th></th></td<>	
point	
ms.l.	
Image: Mark of the second s	
146.35 EX WYE INLET 5.37 451.30 145.53 MANHOLE 6.07 451.50 145.19 GRATE INLET 5.86 450.94 144.90 JUNCTION BOX 1.47 446.16 144.27 60 DEG WYE 2.61 446.58 143.36 60 DEG WYE 2.97 446.50 143.36 60 DEG WYE 3.85 447.38 142.28 60 DEG WYE 5.27 447.08 141.67 60 DEG WYE 5.55 446.86 141.02 60 DEG WYE 7.29 446.82 139.30 JUNCTION BOX 7.80 446.82 139.30 JUNCTION BOX 7.80 446.82 138.61	
H45.53 MANHOLE 6.07 451.50 H45.19 GRATE INLET 5.86 450.94 H44.90 JUNCTION BOX 1.47 446.16 H44.27 60 DEG WYE 2.61 446.58 H43.36 60 DEG WYE 2.97 446.50 H43.36 60 DEG WYE 2.97 446.66 H42.28 60 DEG WYE 2.73 446.66 H42.28 60 DEG WYE 5.27 447.08 H41.67 60 DEG WYE 5.65 446.86 H41.02 60 DEG WYE 7.29 446.85 H33.30 JUNCTION BOX 7.80 446.82 H39.30 JUNCTION BOX 7.80 446.82 H38.61	
H44.90 JUNCTION BOX 1.47 446.16 H44.27 60 DEG WYE 2.61 446.58 H43.93 60 DEG WYE 2.97 446.50 H43.36 60 DEG WYE 3.85 447.38 H42.28 60 DEG WYE 2.73 446.66 H42.28 60 DEG WYE 5.27 447.08 H41.67 60 DEG WYE 5.65 446.86 H41.02 60 DEG WYE 5.65 446.85 H40.41 60 DEG WYE 7.29 446.82 H38.61	MAPSCO 34-1
H44.27 60 DEG WYE 2.61 446.58 H43.93 60 DEG WYE 2.97 446.50 H43.36 60 DEG WYE 3.85 447.38 H42.28 60 DEG WYE 2.73 446.66 H42.28 60 DEG WYE 5.27 447.08 H41.67 60 DEG WYE 5.65 446.86 H41.02 60 DEG WYE 5.65 446.85 H41.02 60 DEG WYE 7.29 446.85 H39.30 JUNCTION BOX 7.80 446.82 H38.61	MAPSCO 34-1
443.93 60 DEG WYE 2.97 446.50 443.36 60 DEG WYE 3.85 447.38 442.89 60 DEG WYE 2.73 446.66 442.28 60 DEG WYE 5.27 447.08 441.67 60 DEG WYE 5.65 446.86 441.02 60 DEG WYE 4.27 444.80 440.41 60 DEG WYE 7.29 446.85 439.30 JUNCTION BOX 7.80 446.82 438.61 Image: Comparison of the second se	
442.89 60 DEG WYE 2.73 446.66 442.28 60 DEG WYE 5.27 447.08 441.67 60 DEG WYE 5.65 446.86 441.02 60 DEG WYE 4.27 444.80 440.41 60 DEG WYE 7.29 446.85 439.30 JUNCTION BOX 7.80 446.82 438.61	
442.28 60 DEG WYE 5.27 447.08 441.67 60 DEG WYE 5.65 446.86 441.02 60 DEG WYE 4.27 444.80 440.41 60 DEG WYE 7.29 446.85 439.30 JUNCTION BOX 7.80 446.82 438.61	
441.02 60 DEG WYE 4.27 444.80 440.41 60 DEG WYE 7.29 446.85 439.30 JUNCTION BOX 7.80 446.82 438.61	
140.41 60 DEG WYE 7.29 446.85 139.30 JUNCTION BOX 7.80 446.82 138.61 Image: Comparison of the temperature of temperat	
138.61 Image: Constraint of the second s	
Image: Market Ma Market Market Mark	
139.17 90 DEG BEND 6.54 445.35	
139.17 90 DEG BEND 6.54 445.35	
Image: second	
REVISIONS	
REV NO. DATE DESCRIPTION	ВҮ
REV NO. DATE DESCRIPTION	BY
	BY
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID	IEERS, LLC
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE ENGIN 221 WEST 6TH ST., SL AUSTIN, TX 7870	IEERS, LLC IITE 800 01
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE ENGIN 221 WEST 6TH ST., SU AUSTIN, TX 7870 PHONE: 512-330-1	IEERS, LLC IITE 800 01 278
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE ENGIN 221 WEST 6TH ST., SL AUSTIN, TX 7870	IEERS, LLC IITE 800 01 278
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE ENGIN 221 WEST 6TH ST., SU AUSTIN, TX 7870 PHONE: 512-330-1 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A N/A	IEERS, LLC ITE 800 D1 278 TRACKING NOS.
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE ENGIN 221 WEST 6TH ST., SL AUSTIN, TX 787 PHONE: 512-330-1 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A WW21-XXX DRAINAGE CALCULATIONS	IEERS, LLC ITE 800 278 TRACKING NOS. DP21-XXXX
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE ENGINERING 221 WEST 6TH ST., SL AUSTIN, TX 787 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A WW21-XXX DRAINAGE CALCULATIONS UTSW BMES UTILITY RELOCATION	IEERS, LLC ITE 800 278 TRACKING NOS. DP21-XXXX
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE ENGINEERS 21 WEST 6TH ST. SL AUSTIN, TX 7870 PHONE: 512-330-1 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A N/A WW21-XXX DRAINAGE CALCULATIONS UTSW BMES UTILITY RELOCATIONS 2300 INWOOD DRIVE 2300 INWOOD DRIVE	IEERS, LLC ITE 800 278 TRACKING NOS. DP21-XXXX
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE ENGINELERS 221 WEST 6TH ST., SL AUSTIN, TX 787/ PHONE: 512-330-1 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A WW21-XXX DRAINAGE CALCULATIONS UTSW BMES UTILITY RELOCATIONS	IEERS, LLC ITE 800 278 TRACKING NOS. DP21-XXXX
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE ENGIN 221 WEST 6TH ST., SU AUSTIN, TX 787 PHONE: 512-330-1 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A WW21-XXX DRAINAGE CALCULATIONS UTSW BMES UTILITY RELOCATIONS 91256 2300 INWOOD DRIVE SOMALE CRAWFORD GRIGSBY SURVEY	IEERS, LLC ITE 800 278 TRACKING NOS. DP21-XXXX
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE ENGIN 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINO.<	IEERS, LLC ITE 800 D1 278 TRACKING NOS. DP21-XXXX DN
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE MARTINEZ MOORE DESCRIPTION 21 WEST 6TH 5T, 787 21 WEST 6TH 5T, 787 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A VALUES CALCULATIONS UTSW BMES UTILITY RELOCATIONS USTAINABLE DEVELOPMENT & CONST	IEERS, LLC ITE 800 D1 278 TRACKING NOS. DP21-XXXX DN
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE 221 WEST 6TH 5T. 3 221 WEST 6TH 5T. 3 221 WEST 6TH 5T. 3 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A W21-XXX DRAINAGE CALCULATIONS UTSW BMES UTILITY RELOCATIONS UTSW BMES UTILITY RELOCATIONS 2300 INWOOD DRIVE CRAWFORD GRIGSBY SURVEY ABSTRACT NO. 533 SUSTAINABLE DEVELOPMENT & CONST	IEERS, LLC ITE 800 D1 278 TRACKING NOS. DP21-XXXX DN ON RUCTION
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE 211 MEST 6TH ST., SG. AUSTIN, TX 787 PHONE: 512-330-1 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A W21-XXX DRAINAGE CALCULATIONS UTSW BMES UTILITY RELOCATION 91256 CRAWFORD GRIGSBY SURVEY ABSTRACT NO. 533 SUSTAINABLE DEVELOPMENT & CONST CTINFORMATION CITY OF DALLAS, DALLAS COUNTY, 1	IEERS, LLC ITE 800 278 TRACKING NOS. DP21-XXXX DN ON RUCTION EXAS
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE 21 WEST 6TH ST., SL AUSTIN, TX 787 PHONE: 512-330-1 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A N/A WW21-XXX DRAINAGE CALCULATIONS UTSW BMES UTILITY RELOCATIONS 91256 CRAWFORD GRIGSBY SURVEY 91256 ABSTRACT NO. 533 SUSTAINABLE DEVELOPMENT & CONST CTINFORMATION CITY OF DALLAS, DALLAS COUNTY, 1 DESIGN DRAWN DESIGN DRAWN	IEERS, LLC ITE 800 D1 278 TRACKING NOS. DP21-XXXX DN ON RUCTION EXAS SHEET
REV NO. DATE DESCRIPTION 02/24/2021 ISSUE FOR BID 02/24/2021 ISSUE FOR BID MARTINEZ MOORE 211 WEST 6TH ST. SU AUSTIN, TX 787 PHONE: 512-330-1 PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING N/A N/A W21-XXX DRAINAGE CALCULATIONS UTSW BMES UTILITY RELOCATION 91256 CRAWFORD GRIGSBY SURVEY ABSTRACT NO. 533 SUSTAINABLE DEVELOPMENT & CONST TINFORMATION CITY OF DALLAS, DALLAS COUNTY, 1	IEERS, LLC ITE 800 278 TRACKING NOS. DP21-XXXX DN ON RUCTION EXAS




STORM DRAINAGE NOTES

- BY PACHECO KOCH, LLC DATED NOVEMBER 2, 2020.
- TRANSPORTATION ADDENDUM.
- THE BIDDING PHASE WILL HAVE NO BEARING ON THE DECISION.

- PSI IF IT IS NECESSARY FOR HAND FINISH.
- (214)-670-6904 TO OBTAIN A PERMIT.
- 8. EXISTING PUBLIC UTILITIES ARE TO REMAIN IN PLACE.
- AND MANHOLES.
- 10. RCP SHALL BE CLASS III.
- INLET BOX AS THE LATERAL DRAINING INLET.
- LATEST EDITION, PAGE 2006.
- ACCESS.

	CONTRACT INFORMATION
CONTRACT NO.	DA
CONTRACTOR	



1. BOUNDARY AND TOPOGRAPHIC SURVEY INFORMATION WAS OBTAINED FROM SURVEY

2. ALL MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION FOR NORTH CENTRAL TEXAS, LATEST EDITION, AND THE CITY OF DALLAS DEPARTMENT OF PUBLIC WORKS AND

3. DURING THE CONSTRUCTION OF THESE IMPROVEMENTS, ANY INTERPRETATION OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION FOR NORTH CENTRAL TEXAS, AND ANY MATTER WHICH REQUIRES THE APPROVAL OF THE OWNER, MUST BE APPROVED BY THE DIRECTOR OF PUBLIC WORKS AND TRANSPORTATION OR HIS DESIGNEE BEFORE ANY CONSTRUCTION INVOLVING THAT DECISION COMMENCES. ASSUMPTIONS ABOUT WHAT THESE DECISIONS MIGHT BE WHICH ARE MADE DURING

4. FOR ADJUSTMENT OF DALLAS WATER UTILITIES APPURTENANCES OR TO VERIFY LOCATIONS OF EXISTING WATER AND WASTEWATER MAINS IN AREA, CALL 214-670-1770 AT LEAST (3) THREE WORKING DAYS PRIOR TO CONSTRUCTION.

5. STREETS, ALLEYS, SIDEWALKS, DRIVEWAYS, AND STORM DRAINAGE FACILITIES IN THE PUBLIC RIGHT-OF-WAY SHALL BE CONSTRUCTED IN CONFORMANCE WITH THE CITY OF DALLAS, STANDARD CONSTRUCTION DETAILS, FILE 251D-1, LATEST EDITION.

6. ALL CONCRETE FOR PAVEMENT SHALL BE 4000 PSI FOR MACHINE FINISH AND 4500


7. A TRAFFIC CONTROL PLAN (TCP) MUST BE SUBMITTED TO THE DEPARTMENT OF TRANSPORTATION FOR REVIEW AND APPROVAL BY THE TRAFFIC SAFETY COORDINATORS PRIOR TO CONSTRUCTION. NO TRAFFIC LANE OR SIDEWALK ALONG THE PUBLIC STREET OR ALLEY IS TO BE CLOSED WITHOUT FIRST OBTAINING THE APPROPRIATE PERMIT(S). CLOSURE OF ANY TRAFFIC LANE MUST BE RESTRICTED TO THE HOURS OF 9:00 A.M. TO 3:30 P.M. WORKDAYS. CONTRACTOR MUST CALL


9. ELEVATIONS OF STORM DRAIN TIE-INS ARE BASED ON SURVEY FLOWLINES OF INLETS

11. MANHOLE COVERS ON INLET BOXES SHOULD BE LOCATED AT THE SAME END OF THE


12. EMBEDMENT MATERIAL FOR ALL PUBLIC STORM DRAINS SHALL BE 1" CRUSHED LIMESTONE, FROM 6" BELOW THE PIPE TO HALF WAY UP THE PIPE SPRING LINE. REFER TO THE CITY OF DALLAS, STANDARD CONSTRUCTION DETAILS, FILE 251D-1,


13. ALL STORM DRAIN LINES MUST BE VIDEOED BY THE CONTRACTOR AFTER THE PAVING WORK ABOVE THE PIPE IS COMPLETE. PLEASE CONFIRM THAT THERE IS ADEQUATE







				REVIS	SIONS		
	REV NO.		DATE		DESCRIPTI	ON	BY
		02/2	24/2021	ISSUE F	OR BID		
				Z MOOR	221	IEZ MOORE ENGINE WEST 6TH ST., SUI AUSTIN, TX 7870 ⁷ PHONE: 512-330-12	FE 800
	PLAT N	0.	BLDG PI	ERMIT NO.	SD&C EN	GINEERING T	RACKING NOS.
Channell Dain	N/A		I	V/A	WW21-	XXX	DP21-XXXX
OF 75 + 2 2 2 202		STO	DRM S	SEWER	R PLAN (DVERAL	L
		UTS	W BM	ES UTI	LITY REI		N
JAMES D. DAVIS JR			2300	INWO	OD DRIV	Έ	
Conservice and a service and a		CRA	WFO	RD GRI	GSBY S	URVEY	
Walter P. Moore and Associates, Inc.			ABS	STRAC ⁻	Γ NO. 53	3	
TBPE Firm Registration No. 1856	SUSTA	INABI	_E DE'	VELOP	MENT &	CONSTR	RUCTION
INFORMATION	CIT	Y OF	DALLA	AS, DAL	LAS CO	UNTY, T	EXAS
DATE	DESIGN	DRAV	WN	DATE	FILE	NUMBER	SHEET
	JDD	VD.	A ^{FE}	BRUARY 2021	311T	XXXX	C09.01





	<u>CONTRACT</u>
CONTRACT NO.	
CONTRACTOR	





_ DATE

REV NO.

PLAT NO.

N/A

DESIGN

JDD

DRAWN

VDA


FEBRUARY

2021

311T


XXXX


C09.02




	LE
	PROPE
	EXIST.
	EXIST.
	PROP.
	PROP.
	PROP.
Ο	PROP.
⊞	PROP.
•	BENCH

	<u>CONTRAC</u>
CONTRACT NO.	
CONTRACTOR	








DATE


REV NO.

PLAT NO.


N/A


" MARKAD an TEt 75"1, 2/2/2024,





	<u>CONTRAC</u>
CONTRACT NO.	
CONTRACTOR	






REV NO.

PLAT NO.


N/A

DESIGN

JDD





	<u>CONTRAC</u>
CONTRACT NO.	
CONTRACTOR	



Ο

⊞





REV NO.

PLAT NO.

N/A

DESIGN

JDD

DRAWN

VDA

FEBRUARY


2021

311T


XXXX

C09.05

465							1					NE A												
460	HM MTS						STA 0+(
455	00 LINE A 556	25		12 LINE A			23 LINE A = X91 CUSTOM 46	20.0		37 LINE A = 00 LAT A-2		2+10.62 LINE A = 0+00.00 LAT A-3	2			17 LINE A = 00 LAT A-4	2			56 LINE A = 00 LAT A-5 88			60 LINE A =	HGL 442.44 HGL 442.89 HGL 442.89
450	STA 0+00.00 INSTALL 8'X6' RIM 443 656	HGL 438.6		STA 0+48 EXIST 12"			STA 1+02.23 INSTALL 9'X9' RIM 446.846	HGL 439.0 HGL 439.0		STA 1+66.37 STA 0+00.00 HGL 439.56		STA 2+10. STA 0+00. HGL 440.5	HGL 441.0			STA 2+80.17 STA 0+00.00 HGL 441.21	HGL 441.6	EX. GRADE		STA 3+33.56 STA 0+00.00 HGL 441.81 HGL 442.28			STA 3+98. STA 0+00.	HGL 442.4 HGL 442.4
445														<u> </u>			<u>/</u>				······································			
440					<u></u>		<u></u> 2			<u></u>														
435					<u>م</u>			6	60" RCP @ 0.80%	0	60" RCP @	0.80%		60" RCP @	0.80%		60	0" RCP @ 0).80%		60	0" RCP @ 0.80	%	
430		54" RCP	60° C	LASS III RCP					CLASS III RCP		60" CLASS I	I RCP		60" CLASS I	III RCP			0" CLASS III				50" CLASS III R		MATCH
425	RCP 433.50 RCP 433.50 RCP 433.50	Q100 = 1 Qc = 232 V100 = 8 Sf = 0.00	65 04 CES	421 '201 433 65 433 65			KCP 434.31 RCP 434.31 RCP 436.18	Q100 = Qc = 23 V100 = Sf = 0.0	64' LF 165.77 CFS 52.93 CFS 8.44 FPS 0041 FT/FT	RCP 434.82 RCP 434.82 RCP 435.32 RCP 435.45	44' LF Q100 = 136.12 (Qc = 232.93 CFS V100 = 6.93 FPS Sf = 0.0028 FT/		Q100 = 1Qc = 232V100 = 6Sf = 0.00	70' LF 33.10 CFS 93 CFS 78 FPS 26 FT/FT	-	CP 435.73 CP 437.36 CP 437.36		53' LF 200 = 23 400 = 23 100 = 23 100 = 23 100 = 23 100 = 23 100 = 23	131.95 CFS 32.93 CFS 6.72 FPS 0026 FT/FT	CCP 436.16 RCP 437.76	3CP 436.29 ∽ < ⊅ ⊅ ⊅	66' LF Q100 = 129.24 Qc = 232.93 C V100 = 6.58 F Sf = 0.0025 FT	CFS FS PS	FL 21" RCP 438.06 FL 60" RCP 436.68
420	FL 60" R 54" R	31 – 0.00	•••••••••••••••••••••••••••••••••••••••	FE 60			FL 60 75 36 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	31 - 0.0	2	Е 00 К Е 60° R Е 21° R	31 – 0.0028 FT/1	<u> </u>		20 FI/FI <u>2</u> C E	5	FL 60" RCP 4	ַרַ	윤 31 – 0.0 [0] 더		FL 60" R FL 21" R	FL 60 [*] R	31 – 0.0023 FI	7.1	FL 21" R FL 60" R
465												NEA		X									Ŧ	
465												NEA		0 JUNCTION BOX			LINE A GRATE INLET					NF NF	TYPE B STN MH	
465 460 455		LINE A =					5	TYPE B STM MH				NEA		NSTALL 10°X10° JUNCTION BOX RIM 450.94 HGL 444.90 HGL 444.90			LINE A GRATE IN					STA 7+76.00 I INF A	INSTALL 6'X6' TYPE B STM MH RIM 451.289 HGL 445.43 HGL 445.53	
460		STA 4+19.27 LINE A = STA 0+00.00 LAT A-7 HGL 442.34 HGL 443.36				4+93.98 LINE A	443.93	STA 5+12.00 LINE A INSTALL 7'X7' TYPE B STM MH RIM 446.165 HGL 443.97 HGL 443.97		EX. GRADE				Sind of 2000 Sind of 2000 BOX INSTALL 10*X10* JUNCTION BOX RIM 450.94 HGL 444.90 HGL 444.90			LINE A GRATE IN	:				CTA 7176 M LINF A	INSTALL 6'X6' TYPE B STM MH RIM 451.289 HGL 445.43 HGL 445.53	
460 455		4+19.27 LINE 0+00.00 LAT 442.94 443.36				4+93.98 LINE A	443.53	5+12.00 ALL 7'X7' 446.165 443.97		EX. GRADE		NEA J-YR HGL		Image: Notice of the state of the			STA 6+94.33 LINE A INSTALL 5'X5' GRATE IN	RIM 451.53 HGL 445.08 HGL 445.19					Install 6'X6' TYPE B STM MH RIM 451.289 RIM 455.43 HGL 445.53 HGL 445.53 HGL 445.53 HGL 445.53	
460 455 450	4	4+19.27 LINE 0+00.00 LAT 442.94 443.36				STA 4+93.98 UNE A	HGL 443.93	STA 5+12.00 INSTALL 7'X7' INSTALL				D-YR HGL		All 450.94 HGL 444.69 HGL 444.90	36" RCP @	0.77%	STA 6+94.33 LINE A	RIM 451.53 HGL 445.08 HGL 445.19	36"		7%		INSTALL 6'X6' TYPE B STM MH RIM 451.289 HGL 445.43 HGL 445.53	
460 455 450 445		DD	00 = 125.85 (= 232.93 CF3	60" RCP @ 	0.80%	STA 4+93.98 LINE A		STA 5+12.00 STA 5+12.00 INSTALL 7'X7' HGL 443.97 HGL 444.77	2 			D-YR HGL		All 450.94 HGL 444.69 HGL 444.90	36" RCP @	0.77%	STA 6+94.33 LINE A	RIM 451.53 HGL 445.08 HGL 445.19	36"	"RCP @ 0.7	7%		INSTALL 6'X6' INSTALL 6'X6' RIM 451.289 HGL 445.53 HGL 445.53	EX. 36"
460 455 450 445 440 435 430 60" CL	LINE STA. 4+	LD CONTRACT	00 = 125.85 (= 232.93 CF3 00 = 6.41 FP3 = 0.0024 FT/	60" RCP @ CFS S S	0.80%	STA 4+93.98 LINE A		STA 5+12.00 STA 5+12.00 NSTALL 7'X7' NNSTALL 7'X7' HGL 443.97 HGL 444.27	2 	54" RC		D-YR HGL		All 450.94 HGL 444.69 HGL 444.90	36" RCP @) 0.77%	STA 6+94.33 LINE A	RIM 451.53 HGL 445.08 HGL 445.19		"RCP @ 0.7	7%		INSTALL 6'X6'	
460 455 450 445 440 435 430 60" CL		LD CONTRACT	00 = 125.85 (= 232.93 CF3 00 = 6.41 FP3 = 0.0024 FT/	60" RCP @ (CFS S S (FT 60" CLASS III 75' LF Q10 Qc Qc V10	0.80%	STA 4+93.98 LINE A		438.09 STA 5+12.00 STA 5+12.00 STA 5+12.00 STA 5+12.00 BIN 446.165 STA 5+12.00 BIN 444.77 HGL 444.77	2 2 2 2 2 2 2 2 2 2 2 2 2 2	54" RC 54" CL 54" CL 22 23 24 24 24 25 24 25 24 25 24 25 25 25 25 25 25 25 25 25 25 25 25 25		D-YR HGL		A066	36" RCP @	0 0.77%	STA 6+94.33 LINE A	RIM 451.53 HGL 445.08 HGL 445.19	36" 36" 36" Q100 Qc = V100	" CLASS III R	7% 		INSTALL 6'X6'	EX. 36" RC Q100 = 30 Qc = 68.6 V100 = 5. Sf = 0.000







VICINITY MAP (N.T.S) MAPSCO 34-HORIZONTAL SCALE: 1"=20' VERTICAL SCALE: 1"=6' BENCHMARKS: BM# 795 A STANDARD WATER DEPARTMENT BENCH MARK SET ON CONCRETE CURB OF STORM SEWER DROP INLET ON THE SOUTHEAST CORNER OF THE INTERSECTION. ESTABLISHED GRID ELEVATION : 442.880 **RECORDED GRID ELEVATION : 442.74** BM# 802 A SQUARE IS CUT ON CENTER OF CONCRETE CURB ON INLET NORTH SIDE OF IRVING BOULEVARD IN FRONT OF BUILDING #2780 IRVING BOULEVARD. ESTABLISHED GRID ELEVATION : 403.78 **RECORDED GRID ELEVATION : 403.77** BM#1 "X " CUT SET ON THE SOUTHEAST EDGE OF A CONCRETE SIDEWALK, ±115 FEET NORTH OF THE NORTHEAST BUILDING CORNER, ±130 FEET SOUTH OF THE CENTERLINE OF INWOOD ROAD AND ±33 FEET WEST OF A CONCRETE DRIVE ENTRANCE. N: 6985868.26, E: 2479190.00, ELEVATION : 445.274 BM# 3 X CUT SET ON A CONCRETE MEDIAN IN INWOOD ROAD, ±300 FEET NORTHEAST OF THE INTERSECTION OF FOREST PARK ROAD AND INWOOD ROAD. N:6986021.72 , E: 2479156.92 , ELEVATION: 440.327 CALL BEFORE YOU DIG! TEXAS ONE CALL PARTICIPANTS REQUEST 48 HOURS NOTICE BEFORE YOU DIG, DRILL, OR BLAST - STOP CALL Texas One Call System CALL 811 REVISIONS BY DATE DESCRIPTION 02/24/2021 ISSUE FOR BID MARTINEZ MOORE ENGINEERS, LLC 221 WEST 6TH ST., SUITE 800 AUSTIN, TX 78701 PHONE: 512-330-1278 MARTINEZ MOORE BLDG PERMIT NO. SD&C ENGINEERING TRACKING NOS. DP21-XXXX N/A WW21-XXX STORM SEWER PROFILE UTSW BMES UTILITY RELOCATION 2300 INWOOD DRIVE CRAWFORD GRIGSBY SURVEY ABSTRACT NO. 533

DRAWN

VDA

DATE

FEBRUARY

2021

FILE


311T


NUMBER


XXXX


SHEET

C09.07










							A REAL PROPERTY OF THE REAL PR	A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR
					20		0 ZONTAL SCALE RTICAL SCALE	
		B	ST(EST REI M# 802 A S IRV EST REI M# 1 " X CE EN M# 3 " X NC	GATHER SET OF THE SET OF SET OF SET SET OF SET SET OF SET	DROP INL RID ELEVA D ELEVATION ARD IN FR RID ELEVA D ELEVATION N THE SOL NORTHEA INWOOD 6985868. N A CONC THE INTEI	ET ON THE TION : 442 ON : 442.74 ITER OF CO CONT OF BL TION : 403 ON : 403.77 JTHEAST EI ST BUILDIN ROAD ANE 26, E: 2475 RETE MEDI RSECTION (SOUTHEAST CORNEL .880 4 NCRETE CURB ON IN JILDING #2780 IRVIN .78 7 DGE OF A CONCRETE IG CORNER, ±130 FE D ±33 FEET WEST OF D190.00, ELEVATION AN IN INWOOD ROA	SIDEWALK, ±115 FEET ET SOUTH OF THE A CONCRETE DRIVE : 445.274
						TEXAS 48 HOU	ALL BEFORE ` ONE CALL PARTICI RS NOTICE BEFORE OR BLAST – STO DS ONE Cal CALL	PANTS REQUEST YOU DIG, DRILL, OP CALL I System
	REV NO.	DATE	E	REVIS	SIONS DE	SCRIPTI	ON	BY
_		02/24/20		ISSUE F				
			I			MARTIN	EZ MOORE ENGINE WEST 6TH ST., SUI	FE 800
							AUSTIN, TX 7870 ⁴ PHONE: 512-330-12	78
	PLAT N N/A					WW21	XXX	RACKING NOS. DP21-XXXX
							DFILE LOCATIC)N
		2	2300 I	NWO	OD I	DRIV	Έ	
				D GRI			URVEY	
	SUSTA							RUCTION
T INFORMATION							UNTY, T	
DATE	DESIGN	DRAWN		UARY			NUMBER	SHEET
	JDD	VDA		021	31	1T	XXXX	C09.08


					ſ	
4	165	LAT	A-5	465	_	465
4	160			460		460
4	155	LAT A-5 =	LINE A LAT A-5 CRATE INLE	455		455
4	150		STA 3+33.56 HGL 442.28 <u>STA 0+13.30</u> INSTALL 4'X4' RIM 447.27 HGL 442.29 HGL 442.29	450		450
4	145	100-YR HGL		445		445
4	140	PROP 21" RCP 32.71%- LAT A-5		440		440
4	135)	435		435
4	130		21" CLASS III RCP 13" LF	430		430
4	125	Q100 = 3.80 CFS Qc = 87.99 CFS	436.16 441 <i>.7</i> 7	425	-	425
4	120	V100 = 1.58 FPS Sf = 0.0006 FT/FT	FL 60" RCP	420		420
	-0-				L	_




465	LAT A-7	465
460		460
455		455
450	STA 0+00.00 LAT STA 0+00.00 LAT STA 0+19.27 LINE HGL 443.35 HGL 443.37 HGL 443.37	450
445	EX. GRADE	445
440	PROP 21" RCP 2.00%- LAT A-7	440
435	21" CLASS III EX. ROOF	435
430	12' LF	430
425	Q100 = 1.86 CFS $\begin{array}{c} & & & & \\ & & & & \\ & & & & \\ Qc = 22.41 CFS \\ & & & & \\ & & & $	425
420	Q100 = 1.86 CFS Qc = 22.41 CFS V100 = 0.77 FPS Sf = 0.0001 FT/FT $= \frac{12}{14}$ $= \frac{12}{14$	420
-0-	+35 0+00 0+	35

	-						
		LA		A	-{	3	
465							465
460					· · · · · · · · ·		460
100						L	100
455			LAT A-8 =	LINE A	LAT A-8	GRATE IN	455
450				STA 4+93.98 HGL 443.93	STA 0+13.17	INSTALL 4'X4 ¹ G RIM 446.56 HGL 443.95	450
445		EX. GRADE — 100-YR HG					445
440	PROP	21" RCP 16.4 LAT A					440
435			ĺ	ſ			435
430						21" CLASS III RCP 13' LF	430
425	Qc =	= 5.96 CFS 66.28 CFS	438.94	437.44	441.06		425
420	V100	= 2.48 FPS 0.0014 FT/FT	FL 21" RCP 438.94	FL 60° RCP 437.44	FL 21" RCP		420
-0-	+35	(ר +C	00	_	0+	35


CONTRACT NO.	
CONTRACTOR	






	CONTRAC
CONTRACT NO.	
CONTRACTOR	

		BN	ST ES RE VI# 802 A IR ES	STANDARD W ORM SEWER I TABLISHED GF CORDED GRIE SQUARE IS CU VING BOULEV TABLISHED GF	ATER DEPARTI DROP INLET OI RID ELEVATION : DELEVATION : DT ON CENTER	N : 442.880 442.74 OF CONCRETE CURB ON I OF BUILDING #2780 IRVI N : 403.78	ER OF THE INTERSECTION. NLET NORTH SIDE OF	
			M#1 ") NG CE EN M#3 ") NG	K " CUT SET ON DRTH OF THE I ENTERLINE OF ITRANCE. N: K " CUT SET ON DRTHEAST OF	N THE SOUTHE NORTHEAST BI INWOOD ROA 6985868.26, E N A CONCRETE THE INTERSEC	AST EDGE OF A CONCRET UILDING CORNER, ±130 F AD AND ±33 FEET WEST O E: 2479190.00, ELEVATIO	EET SOUTH OF THE F A CONCRETE DRIVE N : 445.274	
	DETAILS APP DN PRIVATE DETAILS APP	PROPERT	Y. FIL	.E 251D [.]	N -1	CALL BEFORE TEXAS ONE CALL PARTIC HOURS NOTICE BEFOR OR BLAST – ST Texas One Ca CALL	CIPANTS REQUEST RE YOU DIG, DRILL, TOP CALL	
	REV NO.	DATE		REVIS		RIPTION	BY	
		02/24/20)21	ISSUE FO	OR BID			
			INEZ	MOOR	E	ARTINEZ MOORE ENGIN 221 WEST 6TH ST., SU AUSTIN, TX 787(PHONE: 512-330-1:	ITE 800)1	
S Barry Dai	PLAT NC). BLC	DG PEF	RMIT NO. 4		ENGINEERING		
JAMES D. DAVIS JR								
JAMES D. DAVIS JR 91256 Occ.://CENSE?	UTSW BMES UTILITY RELOCATION 2300 INWOOD DRIVE							
Walter P. Moore and Associates, Inc.						SURVEY		
TBPE Firm Registration No. 1856	SUSTAI				ΓΝΟ. MENT	533 & CONST	RUCTION	
ACT INFORMATION						COUNTY, T		
DATE	DESIGN	DRAWN		<i>ATE</i> RUARY	FILE	NUMBER	SHEET	
	JDD	VDA		O21	311	T XXXX	C09.50	




GENERAL NOTES

- PRIOR TO ANY FIELD CHANGES TO PROPOSEI MATERIALS OR DESIGN, CONTRACTOR SHALL COORDINATE WITH DWU PIPELINE INSPECTION THE ENGINEER OF RECORD. FIELD CHANGES REQUIRE REVISED PLAN REVIEW AND APPROV THE CITY REVIEW ENGINEER AND IS TO BE COORDINATED THROUGH THE DWU PIPELINE INSPECTOR AND ENGINEER OF RECORD.
- ALL WATER MAINS SHALL BE AWWA C900 (D PVC OR CLASS 52 DUCTILE IRON (IN CENTRA BUSINESS DISTRICT, AIRPORTS AND OTHER / DESCRIBED IN THE DWU STANDARDS), WITH WRAP AND FULL BODY FITTINGS.
- WATER AND WASTEWATER EASEMENTS SHALL INCLUDE ADDITIONAL AREA OF WORKING SPA CONSTRUCTION AND MAINTENANCE OF SYSTE 4. ALL WATER DEADHEADS SHALL BE TYPE-K
- COPPER, INSTALLED PER DWU STANDARD DRAWINGS, AND WATER DEADHEADS REFEREN FOLLOWS: N/A TOTAL: N/A. WATER METER AND METERS SHALL BE INSTALLED BY SEPAR PERMIT, ALONG WITH THE CONNECTION TO PE PLUMBING
- WATER METERS/SERVICES SHALL BE LOCATED a. NO LESS THAN 2 FT BEYOND PROPOSED OR AS SHOWN,
- b. NO CLOSER THAN 3 FT (FOR ≤1") OR
- (FOR >1") IN SPACING BETWEEN METERS c. WITHIN PUBLIC SIDEWALK WHERE PRESEN
- OTHER ALLOWABLE PROTECTED LOCATION d. NOT BE INSTALLED IN DRIVEWAYS NOR
- VEHICULAR PATHS. ALL WASTEWATER LATERALS SHALL BE PLAC WITHIN PAVED SIDEWALKS AND NOT WITHIN
- VEHICULAR PATHS, UNLESS OTHERWISE APPR BY DWU INSPECTOR. SIZED AND REFERENCED FOLLOWS: 1-8" LAT TOTAL: P=8" LAT. LATE CLEANOUT SHALL BE INSTALLED BY PERMIT ALONG WITH THE CONNECTION TO PRIVATE PLUMBING.
- ALL 8" THROUGH 15" PVC WASTEWATER MAIN SHALL BE ASTM 3034 (SDR-35), UNLESS NO OTHERWISE. ALL WASTEWATER LATERALS SHA ASTM 3034 (SDR-35), UNLESS NOTED OTHER
- 8. THE MAXIMUM TRENCH WIDTH IS 32" FOR AL DIAMETERS EQUAL TO OR SMALLER THAN 12
- 9. SIDEWALK SHALL MATCH EXISTING WIDTH AND LOCATION.
- 10. THE CERTIFICATE OF ACCEPTANCE (COA) WIL BE ISSUED UNTIL ALL OF THE FOLLOWING ITE HAVE BEEN COMPLETED:
 - a. ALL WATER AND WASTEWATER APPURTEN HAVE BEEN ADJUSTED TO THEIR FINAL AND A FINAL INSPECTION FOR THE P-CONTRACT HAS BEEN SUCCESSFULLY COMPLETED AND;
 - b. THE FINAL PLAT HAS BEEN FILED WITH COUNTY (IF APPLICABLE) AND MATCHES DESIGN PLANS AND;
 - c. ALL FEES OWED TO THE CITY HAVE BEE AND:
- d. A PAY AFFIDAVIT SENT TO PRIVATE DEVELOPMENT STATING THAT THE CONTR HAS BEEN PAID IN FULL.
- FIRE HYDRANTS SHALL BE CONSTRUCTED PE STANDARDS DRAWINGS MANUAL PG. 224. HYDRANTS SHALL BE A MINIMUM OF 2.5' AN MAXIMUM OF 7.5' FROM THE BACK OF CURB 36" OF CLEARANCE FROM ALL OBSTRUCTIONS FIRE HYDRANTS SHALL BE INSTALLED IN ACCORDANCE WITH DWU STANDARDS PRIOR MAIN BEING PLACED IN SERVICE AND THE HYDRANTS PAINTED BY DWU. ANY DELAYS THE RESPONSIBILITY OF THE CONTRACTOR I HYDRANT HAS NOT BEEN INSTALLED PER DW STANDARDS. IT IS RECOMMENDED THAT EXIST CURBS, SIDEWALKS, FINAL GROUND ELEVATIO AND OTHER FEATURES BE STAKED BY THE CONTRACTOR AS NEEDED TO ENSURE COMPL WITH DWU STANDARDS AND AVOID ADDITIONA ADJUSTMENTS OR RELOCATIONS THAT MAY APPROVALS.
- 12. EMBEDMENT FOR WATER MAINS SHALL BE PE CURRENT DWU STANDARD DRAWINGS MANUAL
- 13. WATER MAINS SIZED 12" AND UNDER SHALL MINIMUM OF 4-FT UNDER IMPROVED SURFAC
- AND 6-FT UNDER UNIMPROVED SURFACES. 14. STREET AND ALLEY CUTS WILL FOLLOW THE EDITION OF CITY OF DALLAS DEPARTMENT C PUBLIC WORKS AND TRANSPORTATION "PAVE CUT AND REPAIR STANDARDS MANUAL". ALL AND WASTEWATER SERVICE CUTS IN PAVEME SHALL HAVE THE DITCH LINE FILLED TO PAV BASE LINE WITH LOW STRENGTH FAST FIX
- 15. CONSTRUCTION SPECIFICATIONS AND APPURTENANCES WILL BE COVERED BY THE CURRENT EDITIONS (AS OF THE TIME OF CONSTRUCTION COMMENCEMENT) OF THE FOL MANUALS: DALLAS WATER UTILÍTIES "STANDA DRAWINGS FOR WATER AND WASTEWATER CONSTRUCTION", "STANDARD SPECIFICATIONS PUBLIC WORKS CONSTRUCTION STANDARDS",
- "CITY OF DALLAS ADDENDUM TO THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS WORKS CONSTRUCTION STANDARDS".




CONTRACT NO. CONTRACTOR

							Legender Legender	Bank wind the			
	16.	CONTRACTOR WILL REMOVING METERS NOT USED FOR P REMOVE METERS AND MET NOT DAMAGE THE METER	Roposed Deve Ter Lids in A Nor Lid And I	LOPMENT. WAY AS TO DELIVER				JECT ATION			
VAL BY DR-14)		SALVAGED METERS TO 28 CONTACT ALEX LAND (214 PRIOR TO METER DELIVER' KILL EXISTING DEADHEAD METERS AT THE MAIN LIN	4–670–8213) 4 Y. CONTRACTOR SERVICE FOR R	8-HOURS							
AL AREAS POLY	17.	PRIOR TO THE START OF APPROVED RIGHT OF WAY TRAFFIC CONTROL PLAN, WATER AND WASTEWATER SUBMITTED TO DWU PIPEL	' PERMIT, APPR AND CUT-SHEE INSTALLATION	oved TS for Should be				Y MAP (N.T.S)	MAPSCO 34-T		
L ALSO ACE FOR EM. ICED AS	18.	THE CITY OF DALLAS DEP WORKS WILL APPROVE AN TRAFFIC CONTROL PLAN A CONTACT BETH ADAMS AT	ARTMENT OF P ID/OR DETERMIN AND WORKING H T 214-670-589	UBLIC NE THE IOURS. 96 (NORTH							
CANS RATE PRIVATE	19.	OF I-30), GARY HUGHES AND SOUTH OF I-30), OR CONTRACTOR MAY ONLY L TEMPERATURE IS 36 DEGR SPECIAL METHODOLOGY OF LAYING PIPE AT LESS THA	R CALL (214) 9 LAY PIPE WHEN REES F AND RIS R PROCEDURES	48-4290. SING. ANY FOR							
D CURB 4 FT	20.	THE APPROVAL OF DWU F SUPERINTENDENT. LOW-STRENGTH FLOWABLE BACKFILL MATERIAL AROU	PIPELINE INSPEC	TION							
S NT OR N ANY	21.	LOCATED WITHIN EXISTING ALL NEW MANHOLES OR E AFFECTED BY CONSTRUCT SHALL HAVE THE INTERIOR	EXISTING MANHO ION OF THIS CO R COATED WITH	DLES DNTRACT RAVEN			40	0	40 80		
CED ROVED D AS	22.	405 OR APPROVED EQUAL APPLIED BY CERTIFIED AP OR ROLLER APPLICATION MIL THICKNESS. CONTRACTOR SHALL REPL	PLICATOR. SPR TO A MINIMUM	AY, BRUSH, OF 200				Scale: 1"=4	ł0'		
ERAL		WATER PIPE FITTINGS ENC APPROVED FITTINGS/APPU IT IS THE RESPONSIBILITY HAVE ALL REQUIRED FITTI	COUNTERED WITH JRTENANCES. OF THE CONTF NGS/COUPLING	H NEW DWU RACTOR TO S IN A			WATER N 31-21		WW MAP 31-21S		
ns Ioted All Be Erwise. L Pipes		TIMELY MANNER. ANY DEL AND CONNECTION ISSUES TIE-IN ARE CONSIDERED I SHALL BE BORNE BY THE SPECIALIZED FITTING/COUR	DURING WATER NCIDENTAL WOR CONTRACTOR.	MAIN RK AND [ANY]	BENCHI BM# 795 A		ATER DEPARTMENT	BENCH MARK SET O	N CONCRETE CURB OF		
2". ID	24.	INSTALLED BY QUALIFIED SPECIFIC SKILL. ALL FIRE HYDRANTS SHAL ACCORDANCE WITH DWU S MAIN BEING PLACED IN SE	L BE INSTALLE STANDARDS PRI	d in Or to the	STORM SEWER DROP INLET ON THE SOUTHEAST CORNER OF THE INTERSECTION. ESTABLISHED GRID ELEVATION : 442.880 RECORDED GRID ELEVATION : 442.74 BM# 802 A SQUARE IS CUT ON CENTER OF CONCRETE CURB ON INLET NORTH SIDE OF IRVING BOULEVARD IN FRONT OF BUILDING #2780 IRVING BOULEVARD.						
LL NOT EMS NANCES POSITION		HYDRANTS PAINTED BY D THE RESPONSIBILITY OF T HYDRANT HAS NOT BEEN STANDARDS. IT IS RECOM	WU. ANY DELAY HE CONTRACTO INSTALLED PER MENDED THAT I	'S WILL BE R IF THE ? DWU EXISTING	ESTABLISHED GRID ELEVATION : 403.78 RECORDED GRID ELEVATION : 403.77 BM# 1 " X " CUT SET ON THE SOUTHEAST EDGE OF A CONCRETE SIDEWALK, ±115 FEET NORTH OF THE NORTHEAST BUILDING CORNER, ±130 FEET SOUTH OF THE						
, THE		CURBS, SIDEWALKS, FINAL AND OTHER FEATURES BE CONTRACTOR AS NEEDED WITH DWU STANDARDS AN ADJUSTMENTS OR RELOCA	: STAKED BY TI TO ENSURE CO ND AVOID ADDIT	HE MPLIANCE 10NAL	CENTERLINE OF INWOOD ROAD AND ±33 FEET WEST OF A CONCRETE DRIVE ENTRANCE. N: 6985868.26, E: 2479190.00, ELEVATION : 445.274 BM# 3 " X " CUT SET ON A CONCRETE MEDIAN IN INWOOD ROAD, ±300 FEET NORTHEAST OF THE INTERSECTION OF FOREST PARK ROAD AND INWOOD ROAD. N:6986021.72, E: 2479156.92, ELEVATION: 440.327						
s the En paid	25.	APPROVALS. 5. WATER VALVES SHOULD BE ACCESSIBLE AND READY FOR PERMANENT ACCESSIBILITY BEFORE WATER MAIN CAN BE PLACED IN SERVICE AND TIE-INS COMPLETED. VALVES SHOULD BE PROPERLY									
RACTOR ER DWU	26	BACKFILLED AND PLACED COVERED BY PLATES, BAC CONSTRUCTION MATERIALS ARE NOT ALLOWED. SAWCUT LINES ARE SHOW	CKFILL, OR OTH S. PVC VALVE S	ER STACKS							
ND A 3 WITH S. ALL TO THE		PURPOSES ONLY. CUT AN MUST COMPLY WITH PAVE MANUAL. CONTRACTOR SHALL UNCO	D REPLACEMEN MENT CUT AND	T LIMITS REPAIR WATER							
MLL BE THE MU STING DNS,		MAIN AND CONTACT DWU PRIOR TO CONNECTION. C REQUIRED TO PROVIDE CU POSSIBLY UP TO 2 PIPE O CONDITION IS CONSIDERED	ONTRACTOR MA JT-IN TEE & V/ JOINTS IF EXIST	ALVE AND				CALL 3-1 FOR DWU P LINE LOCA	UBLIC		
LIANCE AL DELAY							TEXAS 48 HOU	ALL BEFORE one call partic jrs notice before or blast – sto as One Ca	IPANTS REQUEST E YOU DIG, DRILL, DP CALL		
ER THE IL. . BE A CES							Ś	CALL	,		
LATEST						REVIS					
EMENT L WATER			REV NO.	DA	ΓĒ		DESCRIPT	ION	BY		
ENT VEMENT				02/24/	2021	ISSUE F	OR BID				
							-	NEZ MOORE ENGINI WEST 6TH ST., SUI AUSTIN, TX 7870 PHONE: 512-330-12	TE 800 1 78		
LLOWING ARD			PLAT NO. BLDG PERMIT NO. SD&C ENGINEERING TRACKING N/A N/A N/A WW20-XXX N/A								
S FOR THE			WA	TER &	WAS	TEWA		/ERALL	PLAN		
PUBLIC			UTSV						CIENCES		
			2300 INWOOD DRIVE								
NOTICE!!!	FACU	WASTEWATER LATERAL		CRAV			GSBY S				
IECTION IN T ITS AT 214-94	HIS DI 48-45	EVELOPMENT. FOR 00. FAILURE TO OBTAIN					Г NO. 53				
		ECTION OF SERVICES					ER UTIL				
		DATE	DESIGN			5, DAL	FILE	UNTY, T	EXAS SHEET		
			JDD	VDA	FEB	RUARY 2021	411Q	XXXX	XXX		





Curb Edge of Pavement R.O.W. Eeasement Storm Sewer/MH Curb Inlet/Grate Inlet Gas Electric Communication Fence Benchmark


CONTRACT NO. CONTRACTOR



2021








Curb Edge of Pavement R.O.W. Eeasement Storm Sewer/MH Curb Inlet/Grate Inlet Gas Electric Communication Fence Benchmark

NOTICE!!! A SEPARATE PERMIT MUST BE OBTAINED FOR EACH WASTEWATER LATERAL AND WATER SERVICE CONNECTION IN THIS DEVELOPMENT. FOR INFORMATION, CONTACT PERMITS AT 214-948-4500. FAILURE TO OBTAIN

CONTRACT INFORMATION CONTRACT NO. CONTRACTOR



MAPSCO 34-


40

BY

XXX

20

WW MAP 31–21S



FEBRUARY

2021


411Q

XXXX

JDD

VDA

MATCHLINE X2 MATCHLINE WW-1 STA 5+01 MATCHLINE W-1 STA 5+28





Curb Edge of Pavement R.O.W. Eeasement Storm Sewer/MH Curb Inlet/Grate Inlet Gas Electric Communication Fence

Benchmark

A SEPARATE PERMIT MUST BE OBT AND WATER SERVICE CONNE INFORMATION, CONTACT PERMIT REQUIRED PERMITS COULD RES

CONTRAC1 CONTRACT NO. CONTRACTOR





					REVIS	SIONS			
- MANAN an	REV NO.		DATE			DESCRIPTI	ON		Γ
5 SAU (21/202)									Γ
		02/2	24/20	21	ISSUE F	OR BID			Γ
JAMES D. DAVIS JR 91256 CENSE Solonal ENG	MARTINEZ MOORE AUSTIN, TX 78701 PHONE: 512-330-1278								
	PLAT N	0.	BLD)G PEF	RMIT NO.	SD&C EN	GINEERIN	G TR/	٩C
Walter P. Moore and Associates, Inc. TBPE Firm Registration No. 1856	N/A			N/	Ά	WW20-	XXX		
	WATER & WASTEWATER PLAN								
	UTSW BIOMEDICAL ENGINEERING & SCIE								
	2300 INWOOD DRIVE								
NOTICE!!!	CRAWFORD GRIGSBY SURVEY								
TAINED FOR EACH WASTEWATER LATERAL ECTION IN THIS DEVELOPMENT. FOR	ABSTRACT NO. 533								
TS AT 214-948-4500. FAILURE TO OBTAIN SULT IN DISCONNECTION OF SERVICES	DALLAS WATER UTILITIES								
T INFORMATION	CIT	Y OF	DA	LLA	S, DAL	LAS CO	UNTY,	TE	X
DATE	DESIGN	DRA	WN	Ľ	DATE	FILE	NUMBER	?	

VDA

JDD


FEBRUARY


2021

411Q

XXXX

XXX






EROSION CONTROL NOTES

- MATERIAL AS CONSTRUCTION PROGRESSES.
- HAVE NOT BEEN FINALLY STABILIZED.
- EXPOSED TO PRECIPITATION C. STRUCTURAL CONTROL MEASURES.
- SPECIFICATIONS.

	CONTRACT INFORMATION
CONTRACT NO.	DA
CONTRACTOR _	



1. BOUNDARY AND TOPOGRAPHIC SURVEY INFORMATION WAS OBTAINED FROM SURVEY BY PACHECO KOCH, LLC DATED NOVEMBER 2, 2020.

2. CONTRACTOR TO FURNISH SWPPP PER TCEQ REQUIREMENTS. THE EROSION CONTROL PLAN AS CONTAINED IN THE DRAWING SET CAN BE USED IN THE STORM WATER POLLUTION PREVENTION PLAN

3. CONTRACTOR SHALL IMPLEMENT INLET PROTECTION DEVISES, REINFORCED FILTER FABRIC BARRIER, STABILIZED CONSTRUCTION ENTRANCES AND OTHER STORM WATER POLLUTION PREVENTION MEASURES AT LOCATIONS SHOWN ON THE PLAN(S) TO KEEP SILT AND/OR EXCAVATED MATERIALS FROM ENTERING THE STORM WATER INLETS AND DITCHES, EVENTUALLY POLLUTING THE RECEIVING STORM SYSTEM. NO HAY BALES WILL BE ALLOWED.

4. DURING THE EXCAVATION/FILL PHASE OF THE PROJECT, CONTRACTOR SHALL SCHEDULE THE WORK IN APPROPRIATE SEGMENTS SO THAT EXCESS MATERIAL CAN BE QUICKLY HAULED AWAY PREVENTING IT FROM STAYING UNCOLLECTED ON THE EXISTING PAVEMENT. ANY LOOSE EXCAVATED MATERIAL WHICH FALLS ON PAVEMENT OR DRIVEWAYS SHALL BE REMOVED APPROPRIATELY.

5. CONTRACTOR SHALL CLEAN UP THE EXISTING STREET INTERSECTIONS AND DRIVEWAYS DAILY AND ADDITIONALLY AS NECESSARY TO REMOVE EXCESS MUD, SOIL, SILT OR ROCK TRACKED FROM THE EXCAVATED AREA.

6. CONTRACTOR SHALL FOLLOW GOOD HOUSEKEEPING PRACTICES DURING THE CONSTRUCTION OF THE PROJECT, ALWAYS CLEANING UP DIRT AND LOOSE

7. CONTRACTOR TO INSPECT AND MAINTAIN THE AREAS LISTED BELOW AT LEAST ONCE EVERY FOURTEEN (14) CALENDAR DAYS AND WITHIN 24 HOURS OF THE END OF A STORM EVENT OF 0.5 INCHES OR GREATER.

A. DISTURBED AREAS OF THE CONSTRUCTION SITE THAT

B. AREAS USED FOR STORAGE OF MATERIALS THAT ARE

D. LOCATIONS WHERE VEHICLES ENTER OR EXIT THE SITE.

 \mathbf{X}

JAMES D. DAVIS JR

91256

. CENSED.


Walter P. Moore and Associates, Inc.

TBPE Firm Registration No. 1856


DATE ____

VONALEN


7. CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING EXISTING DITCHES AND/OR CULVERTS FOR UNOBSTRUCTED DRAINAGE AT ALL TIMES. WHERE SODDING IS DISTURBED BY EXCAVATION ON BACKFILLING OPERATIONS, SUCH AREAS SHALL BE REPLACED BY SEEDING OR SODDING. SLOPES STEEPER THAN 4:1 SHALL BE REPLACED BY BLOCK SODDING. SLOPES STEEPER THAN 3:1 SHALL BE STABILIZED WITH PLANT MATERIALS NOT REQUIRING MOWING FOR MAINTENANCE AND/OR GEOTEXTILE FABRICS AS REQUIRED IN THE PLANS AND





BM# 3 " X " CUT SET ON A CONCRETE MEDIAN IN INWOOD ROAD, ±300 FEET NORTHEAST OF THE INTERSECTION OF FOREST PARK ROAD AND INWOOD ROAD. N:6986021.72 , E: 2479156.92 , ELEVATION: 440.327




				REVIS					
	REV NO. DATE				DESCRIPTI	ON		BY	
		02/24/2	2021	ISSUE F	or Bid				
			TINEZ ^{RS}	MOORE MARTINEZ MOORE ENGINEERS, LLC 221 WEST 6TH ST., SUITE 800 AUSTIN, TX 78701 PHONE: 512-330-1278					
	PLAT N	O. B	_DG PEI	RMIT NO.	SD&C EN	GINEERIN	G TR	ACKING NOS.	
•	N/A		N/	⁄A	WW21-	XXX	L	DP21-XXXX	
~	EROSION CONTROL PLAN								
्लन्	UTSW BMES UTILITY RELOCATION								
	2300 INWOOD DRIVE								
	CRAWFORD GRIGSBY SURVEY								
			ABS	TRAC	T NO. 53	3			
	SUSTAINABLE DEVELOPMENT & CONSTRUCTION								
	CIT	Y OF D	ALLA	S, DAL	LAS CO	UNTY,	TE	XAS	
	DESIGN	DRAWN	Ľ	DATE	FILE	NUMBE	R	SHEET	
	JDD	VDA		RUARY 2021	311T	XXXX	X	C11.01	







- STEEL POSTS WHICH SUPPORT THE SILT FENCE SHALL BE INSTALLED ON A SLIGHT ANGLE TOWARD THE ANTICIPATED RUNOFF SOURCE. POSTS MUST BE EMBEDDED A MINIMUM OF 12"
- THE TOE OF THE SILT FENCE SHALL BE TRENCHED IN WITH A SPADE OR 2. MECHANICAL TRENCHER, SO THAT THE DOWNSLOPE FACE OF THE TRENCH IS FLAT AND PERPENDICULAR TO THE LINE OF THE FLOW. WHERE FENCE CAN NOT BE TRENCHED INTO THE SURFACE (e. g. PAVEMENT) THE FABRIC SHALL BE WEIGHTED DOWN WITH ROCK OR 1" X 4" LUMBER SECURELY FASTENED TO THE SURFACE, ON THE UPSTREAM SIDE TO PREVENT FLOW UNDER THE FENCE.
- THE TRENCH MUST BE A MINIMUM OF 6" DEEP AND 6" WIDE TO ALLOW FOR THE FILTER FABRIC TO BE LAID IN THE GROUND AND BACKFILLED WITH COMPACTED MATERIAL.
- THE FILTER FABRIC SHALL BE SECURELY FASTENED TO THE WOVEN WIRE BACKING, WHICH IN TURN IS SECURELY FASTENED TO THE STEEL FENCE
- 5. ACCUMLUTATED SILT SHALL BE REMOVED WHEN IT REACHES A DEPTH OF 6". THE SILT SHALL BE DISPOSED OF ON AN APPROVED SITE AND IN SUCH A MANNER THAT WILL NOT CONTRIBUTE TO ADDITIONAL SILTRATION.
- INSPECTION SHALL BE MADE WEEKLY AND REPAIR OR REPLACEMENT SHALL BE MADE PROMPTLY, IF NEEDED.
- 7. SILT FENCE SHALL BE REMOVED WHEN THE SITE IS COMPLETELY STABILIZED.





1. DIKES SHALL BE PLACED IN A ROW WITH ENDS TIGHTLY ABUTTING THE ADJACENT DIKE. 2. THE FABRIC COVER AND SKIRT SHALL BE A CONTINUOUS WRAPPING OF NON-WOVEN GEOTEXTILE. THE SKIRT SHALL BE A CONTINUOUS EXTENSION OF THE FABRIC ON THE UPSTREAM FACE. 3. THE SKIRT SHALL BE WEIGHTED WITH A CONTINUOUS LAYER OF 3" X 5" OPEN GRADED ROCK, 1" X 4" LUMBER (SECURELY FASTENED), OR TOED IN 6" WITH MECHANICALLY COMPACTED MATERIAL. OTHERWISE, SHALL BE TRENCED IN 4" IN DEPTIL 4. DIKES AND SKIRT SHALL BE SECURELY ANCHORED IN PLACE USING 6" WIRE STAPLES ON 2' CENTERS ON BOTH EDGES OF SKIRT, OR STAKE USING 3/8" REBAR WITH TEE ENDS. 5. FILTER MATERIAL SHALL BE LAPPED OVER ENDS 67 TO COVER DIKE TO DIKE JOINTS. JOINTS SHALL BE FASTEN WITH GALVANIZED SHOAT RINGS. . THE DIKE STRUCTURE SHALL BE 6 GA. 6"X 6" WIRE MESH, 18" ON A SIDE. 7. ACCUMULATED SILT SHALL BE REMOVED WHEN IT REACHES A DEPTH OF 6" AND DISPOSED OF IN A MANNER WHICH WILL NOT CAUSE ADDITIONAL SILTRATION. 8. INSPECTION SHALL BE MADE WEEKLY AND REPAIR OR REPLACEMENT SHALL

BE MADE PROMPTLY AS NEEDED. 9. AFTER THE SITE IS COMPLETELY STABILIZED, THE DIKES AND ANY REMAINING SILT SHALL BE REMOVED.




EXHIBIT "F"

A STEEL GRID THAT ALLOWS THE SAFE PASSAGE OF VEHICLES WHILE AGITATING THE TIRES TO LOOSEN AND REMOVE THE SOIL BUILD UP. THE GRID OR STRUCTURES SHALL CONFORM TO THE FOLLOWING:

- A. IT SHALL CONSIST OF PIPES OR TUBES SPACED SUCH THAT THERE IS A MINIMUM CLEAR DISTANCE BETWEEN THE PIPES OR TUBES OF 4 ½". IT SHALL BE ELEVATED ABOVE THE GROUND SURFACE A MINIMUM OF 8" TO ALLOW WATER, DEBRIS AND SOIL TO DRAIN.
- MINIMUM DIAMETER OF PIPE OR TUBE SHALL BE 3". C. IT SHALL BE DESIGNED TO SUPPORT ANY AND ALL VEHICLES ENTERING AND LEAVING THE
- CONSTRUCTION SITE. D. IT SHALL BE FIRMLY PLACED IN THE GROUND AT THE EXIT.
- E. IT SHALL BE OF SUFFICIENT LENGTH SO THAT THE AGITATION WILL REMOVE THE SOIL FROM THE TIRES OR A MINIMUM OF 8'-0". F. AT THE "STREET SIDE" APPROACH OF THE GRID THERE SHALL BE AN IMPERVIOUS SURFACE OR IT SHALL CONSIST OF 3" TO 5" DIAMETER ANGULAR CRUSHED STONE/ROCK APPROXIMATELY 5"-0" IN LENGTH, MINIMUM, AND 8" DEEP, MINIMUM. ON THE "JOB SITE" SIDE OF THE GRID, THERE SHALL BE 3" TO 5" DIAMETER ANGULAR CRUSHED STONE/ROCK 15"-0" IN LENGTH, MINIMUM, 8" DEEP, MINIMUM. THE STEEL GRID WILL BE BETWEEN THE "STREET SIDE" APPROACH AND THE JOB SITE CRUSHED STONE/ROCK. ALL CRUSHED STONE/ROCK SHALL HAVE FILTER FABRIC
- BENEATH THE STONE/ROCK. G. STEEL GRID AREA SHALL BE USED AS THE TIRE WASH AREA. WHEN TIRE WASH IS IN USE (RAINY OR MUDDY DAYS) THE AREA SHALL BE MANNED AND THE TIRES SHALL BE WASHED USING A
- HIGH PRESSURE HOSE/NOZZLE. H. THE AREA BENEATH THE GRID SHALL BE SLOPED SUCH THAT DEBRIS, SOIL AND WATER SHALL BE DIVERTED BACK ON TO THE CONSTRUCTION SITE OR TO A SEDIMENT BASIN. NO WATER, SOIL OR DEBRIS SHALL LEAVE THE CONSTRUCTION SITE, THE RESULTING DISCHARGE SHALL BE DISPOSED OF PROPERLY.

	CONTRAC
CONTRACT NO.	
CONTRACTOR	

